

Hydraulic Valve Seat Puller

TEXMA's hydraulic valve seat puller is designed to safely and efficiently remove valve seats from mud pumps. The components are made from premium forged along a throughout heat treatment for center stem and nut in order to sustain high pulling force without mechanical yielding. TEXMA also offers mechanical valve seat pullers upon request.

Features

- TEXMA's puller can exert a force over 200,000 pounds
- Compatible to the most of styles and sizes of API 3 to API 9 valve seats (full open, 3-web, and cross-arm)
- Center stem and nut are made by high strength steel with a throughout heat treatment
- Self-sealing quick disconnect couplings are designed to fit all fluid connectors for quick installation
- Base H-bar is welded with two handles for easy handling
- Both hydraulic and mechanical puller units are available

| TM01016813 | VALVE SEAT PULLER ASSY |
|------------------|--|
| 1.TM01016800 | HYDRAULIC JACK |
| 2.TM01016801 | Center Stem |
| 3.TM01016803 | Center Stem Nut |
| 4.TM01016794 | PULLER H-BAR |
| 5.TM01016804 | Center Bushing |
| 6.TM01016805 | HYDRAULIC HOSE, 3/8"- NPT BOTH B END X LG3000 mm |
| 7.TM01016806 | HYDRAULIC PUMP 10,000PSI, 3/8"-18 NPT-2A |
| 8.TM01016810 | 3/8"NPT COUPLER |
| 9.TM01016808 | GAUGE ADAPTER |
| 10.TM01016809 | GAUGE 0~14K PSI (100 MPa) |
| 11.TM01016811 | 1/4"-NPT MALE ADAPTER,M14X1.5 |
| 12.TM01016812 | SEAL MAT Ø12 |
| 13.TM01016834 | CARRYING CASE |
| 14.Variable size | PULLER HEADS 3"~ 7" 60 TON (NOT INCLUDED) |





